

CEMENT ADD P



DESCRIPTION

CEMENT ADD P is a safe additive designed to control the release of salts from concrete products, greatly increasing their market appeal and durability. CEMENT ADD P reacts with soluble salts in the cement-aggregate matrix and prevents them from migrating as soluble salts to the surfaces of finished products. CEMENT ADD P also acts as a cement dispersion agent, allowing for reduced water content in mixes, leading to faster mould turn around and stronger product.

APPLICATIONS

CEMENT ADD P is used as an additive in the manufacture of cement masonry products such as concrete pavers, bricks and blocks. CEMENT ADD P can also be used as an additive for renders, floats and premix concrete for slabs etc.

BENEFITS

No unsightly chalking on finished products.
Improved aesthetics, brighter, even colours.
Improved structural integrity of products.
Minimal cost per mix.

PRODUCT USAGE

WET MIX PAVING

As a guide, 1 kg of CEMENT ADD P is added per 100kg of cement. Depending on water-cement ratios and cement-aggregate ratios, the 1 kg can be increased or decreased depending on the amount of lubricity required.

DRY MIX PAVING

As a guide, 500 grams of CEMENT ADD P is added per 100kg of cement. Depending on water-cement ratios and cement-aggregate ratios, the 1 kg can be increased or decreased depending on the amount of lubricity required.

SAND FINISH RENDER

As a guide, 300 grams of CEMENT ADDP is added per bag of cement based on a 1:4 cement/sand render. Half the normal water should be added to the mix prior to adding CEMENT ADD P. Let mix, then add water to achieve the desired slump.

SAND/CEMENT FLOATS

As a guide, 300 grams of CEMENT ADDP is added per bag of cement based on a 1:5-6 cement/sand render. Half the normal water should be added to the mix prior to adding CEMENT ADD P. Let mix, then add water to achieve the desired slump.

STORAGE

Store CEMENT ADD P in sealed containers under cover in a cool area away from foodstuffs.

CLEAN UP

Clean up CEMENT ADD P by broom in dry state or water if wet.

PACK SIZES

CEMENT ADD P is sold in packs of 10kg.

TRANSPORT

CEMENT ADD P is not a hazardous product for transport under the guidelines of WORKSAFE AUSTRALIA.

FACTORY
16 GOONGARRIE STREET
BAYSWATER WA 6053
AUSTRALIA

POSTAL
PO BOX 385
BAYSWATER WA 6933
AUSTRALIA

TELEPHONE
TEL. (08) 9378 2022
FAX. (08) 9377 2575
MOB. 0418 956 860

IDENTIFICATION
PAGE 1 of 1
ISSUE: JULY 2011
REF: CADP

QUINDALUP HOLDINGS PTY LTD (A.C.N. 009 026 386) AS TRUSTEE FOR CALMARC FAMILY TRUST (ABN 18 340 289 669)

This information is offered solely for the customer and/or specifier for their consideration, investigation and verification. The suggestions mentioned herein should be fully assessed prior to application. No warranty or implied liability is given for any recommendations, advice, suggestions made by Calmarc Chemicals or representatives, agents or distributors for the conditions of use and labour for the products which are beyond our control. Catalogue or specification contents may change from time to time without notice. M.S.D.S. is available.