

MARCMOVE



DESCRIPTION

MARCMOVE is a mixture of selected low odour solvents combined with emulsifying detergents so that MARCMOVE treated residues can be removed by flushing or rinsing with a water jet. This method removes the residue and MARCMOVE as an emulsion.

USES

MARCMOVE is suitable for removing:
Mineral oils and greases from concrete or metal.
Most adhesives and some forms of coatings.
Clean up surface residue after using paint strippers.
Removal of acrylic or PVA coatings and sealers.
Removal of graffiti.

DIRECTIONS

DEGREASING, GRAFFITI AND PAINT RESIDUE REMOVAL: Apply MARCMOVE to the substance to be removed (if possible scrub it in). Leave for 5-10 minutes then hose the treated area while scrubbing. Hosing with high-pressure hot water is excellent. If there are stubborn deposits to remove, repeat the process after drying the treated area.

ADHESIVES: In most cases MARCMOVE is applied as a dilution (up to 1 : 1) with water to the adhesive. Allow it to work for 5 - 10 minutes. After this time, test a section of adhesive to determine effectiveness. If ready to remove, use a scraper to remove the softened adhesive. Rinse the floor with hot water containing a little detergent.

REMOVING SEALERS AND POLISHERS: Vinyl sheet tiles, ceramic tiles with old sealers or polish on them can be removed by treating small areas at a time with MARCMOVE. Brush it around and wipe off with a rag. Rinse the cleaned area with warm water. Continue over the whole area in this fashion.

When dry, reseal with two coats of BRYLCOTE, CALICONE, WETLOOK or ECO-FINISH.

CAUTION: Test a small section of vinyl with MARCMOVE to ensure that MARCMOVE does not dissolve or damage the substrate to be cleaned. When dry, reseal with two coats of BRYLCOTE, CALICONE or WETLOOK SEALER.

CAUTION: MARCMOVE can soften some plastics and affect painted surfaces, vinyl tiles and sheet. Any form of after treatment to the cleaned substrate should not be undertaken until the substrate is thoroughly dry and all the solvents have dissipated.

SAFETY

When using MARCMOVE, especially indoors, ensure good ventilation is maintained. Wear gloves, goggles, protective clothing and a half face mask with solvent cartridge if nausea occurs or effective air movement is not possible.

CLEAN UP

Clean up with water.

STORAGE

Store MARCMOVE under cover in a cool place, away from foodstuffs, heat sources and flames.

PACK SIZES

MARCMOVE is sold in packs of 5, 20 and 200 litres.

TRANSPORT

Flammable liquid : CLASS : 3 : SUBCLASS : none :
U.N. No. 1268 : F/PT 7°C : Contains petroleum distillates n.o.s. : STORE AWAY FROM FLAME, HEAT, FOOD : Packaging : GROUP II & III Metal containers : HAZCHEM 3[Y]E. IERG. No. 14.

FACTORY
16 GOONGARRIE STREET
BAYSWATER WA 6053
AUSTRALIA

POSTAL
PO BOX 385
BAYSWATER WA 6933
AUSTRALIA

TELEPHONE
TEL. (08) 9378 2022
FAX. (08) 9377 2575
MOB. 0418 956 860

IDENTIFICATION
PAGE 1 of 1
ISSUE: JULY 2011
REF: MCMV

QUINDALUP HOLDINGS PTY LTD (A.C.N. 009 026 386) AS TRUSTEE FOR CALMARC FAMILY TRUST (ABN 18 340 289 669)
This information is offered solely for the customer and/or specifier for their consideration, investigation and verification. The suggestions mentioned herein should be fully assessed prior to application. No warranty or implied liability is given for any recommendations, advice, suggestions made by Calmarc Chemicals or representatives, agents or distributors for the conditions of use and labour for the products which are beyond our control. Catalogue or specification contents may change from time to time without notice. M.S.D.S. is available.