

# WET LOOK SEALER



## DESCRIPTION

WET LOOK is a pure acrylic sealer, designed to enhance and protect masonry surfaces. On drying, WET LOOK produces a classic wet look finish, with an appealing gloss level.

## SURFACES

Slate  
Stone  
Clay and concrete paving  
exposed aggregate (both poured and paving bricks)  
clay brick, concrete block and reconstituted  
limestone walls (sacrificial anti graffiti)

## PREPARATION

The surface should be free of dust, dirt, oil, mould, algae, fungi, laitence and should have a sound, firm surface which does not give way when given the packaging tape adhesion test. Allow the surface to dry thoroughly after water blasting with a high pressure machine or normal washing before applying WET LOOK. Surfaces should be allowed to dry for a minimum of 48 hours @25°C. Residual moisture in the substrate can have a detrimental effect on WET LOOK SEALER.

## DIRECTIONS

Use WET LOOK as supplied if applying by brush or roller(short knap recommended). Stir thoroughly before use. If spraying WET LOOK use as supplied if equipment is suitable to spray it. Coverage of WET LOOK as supplied is 5-7m<sup>2</sup>/litre/coat. If being used as a semi sacrificial graffiti coating, coverage of WET LOOK as supplied is 5-6m<sup>2</sup>/litre/coat. A MINIMUM of two coats is recommended.

Most applications require two coats of WET LOOK. Allow full drying of the applied coating before applying subsequent coats. Drying is dependant on situation (internal or external) and weather

conditions. Heavy duty applications will require three or four coats.

Damaged areas of WET LOOK can be removed with MARCMOVE and recoated as done originally.

Do not apply is rain or inclement weather has passed or is expected within 72 hours.

## CLEAN UP

Use MARCMOVE to remove WET LOOK in the wet or dry state.

## SAFETY & STORAGE

Wear safety boots, glasses and protective clothing. Have good ventilation if using indoors or wear a mask with a solvent cartridge. Store under cover away from flame and heat sources.

## PACK SIZES

WET LOOK is sold in packs of 20 and 200 litres.

## TRANSPORT

FLAMMABLE LIQUID : UN No 1866 : CLASS 3 :  
PACKAGING GROUP III : METAL CONTAINER :  
HAZCHEM 3(Y) : I.E.R.G. No 14

FACTORY  
16 GOONGARRIE STREET  
BAYSWATER WA 6053  
AUSTRALIA

POSTAL  
PO BOX 385  
BAYSWATER WA 6933  
AUSTRALIA

TELEPHONE  
TEL. (08) 9378 2022  
FAX. (08) 9377 2575  
MOB. 0418 956 860

IDENTIFICATION  
PAGE 1 of 1  
ISSUE: JULY 2011  
REF: WTLK

QUINDALUP HOLDINGS PTY LTD (A.C.N. 009 026 386) AS TRUSTEE FOR CALMARC FAMILY TRUST (ABN 18 340 289 669)

This information is offered solely for the customer and/or specifier for their consideration, investigation and verification. The suggestions mentioned herein should be fully assessed prior to application. No warranty or implied liability is given for any recommendations, advice, suggestions made by Calmarc Chemicals or representatives, agents or distributors for the conditions of use and labour for the products which are beyond our control. Catalogue or specification contents may change from time to time without notice. M.S.D.S. is available.